Integrated Device Technology, Inc.

3.3V CMOS OCTAL D REGISTERS (3-STATE)

IDT54/74FCT3574/A
ADVANCE INFORMATION

FEATURES:

- 0.5 MICRON CMOS Technology
- ESD > 2000V per MIL-STD-883, Method 3015; > 200V using machine model (C = 200pF, R = 0)
- 25 mil Center SSOP Packages
- Extended commercial range of -40°C to +85°C
- V_{CC} = 3.3V ±0.3V, Normal Range or V_{CC} = 2.7V to 3.6V, Extended Range
- CMOS power levels (0.4µW typ. static)
- Rail-to-Rail output swing for increased noise margin
- Military product compliant to MIL-STD-883, Class B

DESCRIPTION:

The FCT3574/A are 8-bit registers built using an advanced dual metal CMOS technology. These registers consist of eight D-type flip-flops with a buffered common clock and buffered 3-state output control. When the output ($\overline{OE}$) input is LOW, the eight outputs are enabled. When the $\overline{OE}$ input is HIGH, the outputs are in the high-impedance state.

Input data meeting the set-up and hold time requirements of the D inputs is transferred to the O outputs on the LOW-to-HIGH transition of the clock input.

FUNCTIONAL BLOCK DIAGRAM



3095 drw 01

PIN CONFIGURATION



DIP/SOIC/SSOP
TOP VIEW

3095 drw 02

PIN DESCRIPTION

Pin Names	Description
D_N	D flip-flop data inputs
CP	Clock Pulse for the register. Enters data on LOW-to-HIGH transition.
O_N	3-state outputs, (true)
$\overline{O}_N$	3-state outputs, (inverted)
$\overline{OE}$	Active LOW 3-state Output Enable input

3095 tbl 01

The IDT logo is a registered trademark of Integrated Device Technology, Inc.

©1995 Integrated Device Technology, Inc.

FUNCTION TABLE (1)

Function	Inputs			Outputs	Internal
	$\overline{OE}$	CP	D_N	O_N	$\overline{Q}_N$
HI-Z	H	L	X	Z	NC
	H	H	X	Z	NC
LOAD	L	↑	L	L	H
REGISTER	L	↑	H	H	L
	H	↑	L	Z	H
	H	↑	H	Z	L

3095 tbl 02

NOTE:
1. H = HIGH Voltage Level
   L = LOW Voltage Level
   X = Don't Care
   Z = High Impedance
   NC = No Change
   ↑ = LOW-to-HIGH transition

CAPACITANCE (T_A = +25°C, f = 1.0MHz)

Symbol	Parameter(1)	Conditions	Typ.	Max.	Unit
C_{IN}	Input Capacitance	V_{IN} = 0V	3.5	6.0	pF
C_{OUT}	Output Capacitance	V_{OUT} = 0V	4.0	8.0	pF

3095 tbl 04

NOTE:
1. This parameter is measured at characterization but not tested.

ABSOLUTE MAXIMUM RATINGS(1)

Symbol	Rating	Commercial	Military	Unit
V_{TERM}(2)	Terminal Voltage with Respect to GND	–0.5 to +4.6	–0.5 to +4.6	V
V_{TERM}(3)	Terminal Voltage with Respect to GND	–0.5 to +7.0	–0.5 to +7.0	V
V_{TERM}(4)	Terminal Voltage with Respect to GND	–0.5 to V_{CC} + 0.5	–0.5 to V_{CC} + 0.5	V
T_A	Operating Temperature	–40 to +85	–55 to +125	°C
T_{BIAS}	Temperature Under Bias	–55 to +125	–65 to +135	°C
T_{STG}	Storage Temperature	–55 to +125	–65 to +150	°C
P_T	Power Dissipation	1.0	1.0	W
I_{OUT}	DC Output Current	–60 to +60	–60 to +60	mA

3095 lnk 03

NOTES:
1. Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.
2. Vcc terminals.
3. Input terminals.
4. Output and I/O terminals.

DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE

Following Conditions Apply Unless Otherwise Specified:
Commercial: T_A = –40°C to +85°C, V_{CC} = 2.7V to 3.6V; Military: T_A = –55°C to +125°C, V_{CC} = 2.7V to 3.6V

Symbol	Parameter	Test Conditions[1]		Min.	Typ.[2]	Max.	Unit
V_{IH}	Input HIGH Level (Input pins)	Guaranteed Logic HIGH Level		2.0	—	5.5	V
	Input HIGH Level (I/O pins)			2.0	—	V_{CC}+0.5	
V_{IL}	Input LOW Level (Input and I/O pins)	Guaranteed Logic LOW Level		–0.5	—	0.8	V
I_{IH}	Input HIGH Current (Input pins)[6]	V_{CC} = Max.	V_I = 5.5V	—	—	±1	µA
	Input HIGH Current (I/O pins)[6]		V_I = V_{CC}	—	—	±1	
I_{IL}	Input LOW Current (Input pins)[6]		V_I = GND	—	—	±1	
	Input LOW Current (I/O pins)[6]		V_I = GND	—	—	±1	
I_{OZH}	High Impedance Output Current	V_{CC} = Max.	V_O = V_{CC}	—	—	±1	µA
I_{OZL}	(3-State Output pins)[6]		V_O = GND	—	—	±1	
V_{IK}	Clamp Diode Voltage	V_{CC} = Min., I_{IN} = –18mA		—	–0.7	–1.2	V
I_{ODH}	Output HIGH Current	V_{CC} = 3.3V, V_{IN} = V_{IH} or V_{IL}, V_O = 1.5V[3]		–36	–60	–110	mA
I_{ODL}	Output LOW Current	V_{CC} = 3.3V, V_{IN} = V_{IH} or V_{IL}, V_O = 1.5V[3]		50	90	200	mA
V_{OH}	Output HIGH Voltage	V_{CC} = Min.	I_{OH} = –0.1mA	V_{CC}–0.2	—	—	V
		V_{IN} = V_{IH} or V_{IL}	I_{OH} = –3mA	2.4	3.0	—	
		V_{CC} = 3.0V, V_{IN} = V_{IH} or V_{IL}	I_{OH} = –6mA MIL. I_{OH} = –8mA COM'L.	2.4[5]	3.0	—	
V_{OL}	Output LOW Voltage	V_{CC} = Min.	I_{OL} = 0.1mA	—	—	0.2	V
		V_{IN} = V_{IH} or V_{IL}	I_{OL} = 16mA	—	0.2	0.4	
			I_{OL} = 24mA	—	0.3	0.55	
		V_{CC} = 3.0V, V_{IN} = V_{IH} or V_{IL}	I_{OL} = 24mA	—	0.3	0.50	
I_{OS}	Short Circuit Current[4]	V_{CC} = Max., V_O = GND[3]		–60	–135	–240	mA
V_H	Input Hysteresis	—		—	150	—	mV
I_{CCL} I_{CCH}	Quiescent Power Supply Current	V_{CC} = Max., V_{IN} = GND or V_{CC}	COM'L.	—	0.1	10	µA
I_{CCZ}			MIL.	—	0.1	100	

3095 lnk 05

NOTES:

1. For conditions shown as Max. or Min., use appropriate value specified under Electrical Characteristics for the applicable device type.
2. Typical values are at Vcc = 3.3V, +25°C ambient.
3. Not more than one output should be tested at one time. Duration of the test should not exceed one second.
4. This parameter is guaranteed but not tested.
5. V_{OH} = V_{CC} –0.6V at rated current.
6. The test limits for this parameter is ± 5µA at T_A = –55°C.

POWER SUPPLY CHARACTERISTICS

Symbol	Parameter	Test Conditions[1]		Min.	Typ.[2]	Max.	Unit
ΔI_{CC}	Quiescent Power Supply Current	V_{CC} = Max.	$V_{IN} = V_{CC} - 0.6V$[3]				mA
I_{CCD}	Dynamic Power Supply Current[4]	V_{CC} = Max. Outputs Open $\overline{OE}$ = GND 50% Duty Cycle One Input Toggling	$V_{IN} = V_{CC}$ V_{IN} = GND				µA/ MHz
I_C	Total Power Supply Current[6]	V_{CC} = Max. Outputs Open f_{CP} = 10MHz 50% Duty Cycle	$V_{IN} = V_{CC}$ V_{IN} = GND				mA
		$\overline{OE}$ = GND fi = 5MHz 50% Duty Cycle One Bit Toggling	$V_{IN} = V_{CC} - 0.6V$ V_{IN} = GND				
		V_{CC} = Max. Outputs Open f_{CP} = 10MHz 50% Duty Cycle	$V_{IN} = V_{CC}$ V_{IN} = GND				
		$\overline{OE}$ = GND fi = 2.5MHz 50% Duty Cycle Eight Bits Toggling	$V_{IN} = V_{CC} - 0.6V$ V_{IN} = GND				

3095 tbl 06

NOTES:

1. For conditions shown as max. or min., use appropriate value specified under Electrical Characteristics for the applicable device type.
2. Typical values are at V_{CC} = 3.3V, +25°C ambient.
3. Per TTL driven input; all other inputs at V_{CC} or GND.
4. This parameter is not directly testable, but is derived for use in Total Power Supply Calculations.
5. Values for these conditions are examples of the I_{CC} formula. These limits are guaranteed but not tested.
6. $I_C = I_{QUIESCENT} + I_{INPUTS} + I_{DYNAMIC}$
   $I_C = I_{CC} + \Delta I_{CC} D_H N_T + I_{CCD} (f_{CP} N_{CP}/2 + f_i N_i)$
   I_{CC} = Quiescent Current (I_{CCL}, I_{CCH} and I_{CCZ})
   ΔI_{CC} = Power Supply Current for a TTL High Input
   D_H = Duty Cycle for TTL Inputs High
   N_T = Number of TTL Inputs at D_H
   I_{CCD} = Dynamic Current Caused by an Input Transition Pair (HLH or LHL)
   f_{CP} = Clock Frequency for Register Devices (Zero for Non-Register Devices)
   N_{CP} = Number of Clock Inputs at f_{CP}
   f_i = Input Frequency
   N_i = Number of Inputs at f_i

SWITCHING CHARACTERISTICS OVER OPERATING RANGE[3]

			FCT3574				FCT3574A				
			Com'l.		Mil.		Com'l.		Mil.		
Symbol	Parameter	Conditions[1]	Min.[2]	Max.	Min.[2]	Max.	Min.[2]	Max.	Min.[2]	Max.	Unit
t_{PLH} t_{PHL}	Propagation Delay CP to O_N[3]	C_L = 50pF R_L = 500Ω	2.0	10.0	2.0	11.0	2.0	6.5	2.0	7.2	ns
t_{PZH} t_{PZL}	Output Enable Time		1.5	12.5	1.5	14.0	1.5	6.5	1.5	7.5	ns
t_{PHZ} t_{PLZ}	Output Disable Time		1.5	8.0	1.5	8.0	1.5	5.5	1.5	6.5	ns
t_{SU}	Set-up Time HIGH or LOW, D_N to CP		2.0	—	2.0	—	2.0	—	2.0	—	ns
t_H	Hold Time HIGH or LOW, D_N to CP		1.5	—	1.5	—	1.5	—	1.5	—	ns
t_W	CP Pulse Width HIGH or LOW		7.0	—	7.0	—	5.0	—	6.0	—	ns

3095 tbl 07

NOTES:
1. See test circuit and waveforms.
2. Minimum limits are guaranteed but not tested on Propagation Delays.
3. Propagation Delays and Enable/Disable times are with V_{CC} = 3.3V ±0.3V, Normal Range. For V_{CC} = 2.7V to 3.6V, Extended Range, all Propagation Delays and Enable/Disable times should be degraded by 20%.

TEST CIRCUITS AND WAVEFORMS

TEST CIRCUITS FOR ALL OUTPUTS



3095 drw 03

SWITCH POSITION

Test	Switch
Open Drain Disable Low Enable Low	6V
Disable High Enable High	GND
All Other tests	Open

3095 lnk 08

DEFINITIONS:

C_L= Load capacitance: includes jig and probe capacitance.
R_T = Termination resistance: should be equal to Z_{OUT} of the Pulse Generator.

SET-UP, HOLD AND RELEASE TIMES



3095 drw 04

PULSE WIDTH



3095 srw 05

PROPAGATION DELAY



3095 drw 06

ENABLE AND DISABLE TIMES



3095 drw 07

NOTES:

1. Diagram shown for input Control Enable-LOW and input Control Disable-HIGH.
2. Pulse Generator for All Pulses: Rate ≤ 1.0MHz; t_F ≤ 2.5ns; t_R ≤ 2.5ns.
3. If V_{CC} is below 3V, input voltage swings should be adjusted not to exceed V_{CC}.

ORDERING INFORMATION



3095 drw 08

WWW.ALLDATASHEET.COM

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

www.AllDataSheet.com

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com